

35 MacDonald Ave, Dartmouth, NS, B3B 1C6 Tel: 902 468 6696 Toll Free NS: 1 800 971 3888

Fax: 902 468 8843

Web: www.constructionsafetyns.ca

Sample General Safe Work Practice for Chipper

- Safety devices and controls, such as emergency shut-off devices, are tested and verified to be functioning properly before the chipper is used.
- Workers are trained in safe work procedures, including operating wood chipper safety devices and safety controls. These procedures should be based on the <u>manufacturer's</u> recommendations for each machine.
- At least two workers are in close contact with each other when operating the chipper.
- Workers wear <u>close-fitting clothing</u>, gloves without cuffs, trousers without cuffs, and <u>skid-resistant foot wear</u>. Clothing should be kept tucked in.
- Workers' hands and feet remain outside the infeed hopper.
- Workers feed brush and limbs into the infeed hopper butt end first.
- Workers feeding material are positioned at the side of the machine to allow quick operation of the emergency shut-off device and minimize risk of entanglement in branches. Because of differences among machines, the manufacturer's operating manual should be consulted for guidance. Safe feeding of some disc-type chippers requires the worker to be on the right side.
- Workers walk away once the feed mechanism has grabbed the material.
- Workers lay short material on top of longer material that's feeding or use a longer branch to push it through the infeed hopper.
- Workers load small raked-up material such as twigs and leaves directly into the chip truck or in trash cans or bags instead of feeding it into the chipper.
- Workers keep the area around the wood chipper free of slipping and tripping hazards.
- Workers wear hard hats, eye protection and hearing protection.