

35 MacDonald Ave, Dartmouth, NS, B3B 1C6 Tel: 902 468 6696

Toll Free NS: 1 800 971 3888 Web: www.constructionsafetyns.ca

SAFE WORK PRACTICE

Name of Job:	Development Date:	Developed By:	Approved E	By: Review Date:
Use and Handling				
of Propane Tanks				
Possible Hazards Present				
Compressed gas	Fire/Explosion	Heavy Lifting		
Personal Protective Equipment (PPE) and Devices Recommended				
Steel toed boots	Hand protection	Eye Protectio	n F	ire retardant clothes

- **DO** use Nylon slings in a "choker" fashion when loading, off-loading or lifting propane tanks.
- **DO NOT** use "Lifting lugs" provided on tanks. Slings are to be wrapped around the shell of the tank.
- **DO** use Regulators are to be removed from the tank prior to any movement of the tank.
- **DO** ensure tank caps are in place when not hooked up.
- **DO** use Crane hooks shall be equipped with a "safety latch".
- **DO** equip All trucks, cranes or equipment used to handle propane tanks with a fire extinguisher appropriate for the size and type of tank being handled.
- **DO NOT** except in an emergency, any movement or repositioning of tanks shall be performed by a competent worker.
- **DO NOT** Tanks are not to be heated to increase flow.
- **DO** when in use, propane bottles are to securely held in an upright position.
- **DO** NOT Tanks are not to be hooked up and used without proper regulators.

Please note: This document is for information purposes only as a guide. The safe job procedures (SJP) and safe work practices (SWP) created for your workplace should reflect your organizations processes, equipment and hazards as identified by a hazard analysis. Construction Safety Nova Scotia does not assume responsibility for the use of information in this document. If assistance is needed to complete a SWP and SJP for your organization please contact CSNS member services at constructionsafetyns.ca or 1.800.971.3888.